



ISO-9001 Registered Quality System.  
ISO-21469 Certified

**Sales, Service & Distribution Center**  
Newark, NJ 07105  
Phone: 973-589-9150 Fax: 973-589-4432

**Manufacturing, Sales, Service & Distribution Center**  
Toledo, OH 43605  
Phone: 419-691-2491 Fax: 419-693-3806

**Sales and Tech Service Support**  
Phone: 1-800-733-4755

## PRODUCT DATA

# LUBRIPLATE SYNXTREME ASAP

## ANTI-SEIZE ASSEMBLY PASTE

### DESCRIPTION

LUBRIPLATE SYNXTREME ASAP is our premium anti-seize compound composed of a food grade, high-heat-resistant carrier fortified with rust and corrosion inhibitors and antioxidants. It is designed to lubricate and protect threaded connections and flanges at temperatures to 1,800°F (982°C) and under extreme load pressure conditions.

LUBRIPLATE SYNXTREME ASAP does not separate. It is non-dripping, non-hardening, permits easy disassembly and removal of connection even after lengthy service or severe conditions. Stress, strain, and time to disassemble are greatly diminished.

### APPLICATIONS

LUBRIPLATE SYNXTREME ASAP applications include all Nuts and Bolts, Bushings, Centers, Cam Rollers, Conveyors, Couplings, Dies, Drills and Taps, Fittings, Flanges, Gears and Motors, Keyways, Press Fits, Pumps, Shafts, Sleeves and Slides, Spark Plugs, Valves, and Wristpins

### ADVANTAGES

- ⇒ Protects parts from seizing and rusting together
- ⇒ Greatly reduces Maintenance Headaches caused by parts rusting together
- ⇒ Aids in assembly and disassembly of parts
- ⇒ Highly resistant to saltwater corrosion
- ⇒ Compatible with all types of metals/most plastics

### CAUTIONS

Read all information on labels and Safety Data Sheets prior to use. All products should be tested and evaluated for a particular purpose prior to use.

### Typical Test Data

PROPERTY	TEST METHOD	TYPICAL RESULTS*
Specific Gravity		1.2
Weight per gallon		10.0 LB
Penetration Range		280 - 400
Oil Separation, 30 hr. at 158°F		1%
Flash Point	ASTM D-92-85	>400°F
Color		White
Friction Coefficient		0.10
Homogeneity		Will not settle, harden or separate under normal conditions
Carrier plus Additive		65%
Solid Lubricants		35%
RoHS		Compliant

### SERVICE RECOMMENDATIONS

-30°F to 1800°F (-184°C to 982°C)

### STORAGE RECOMMENDATIONS

- ⇒ Products should be stored between 40°F-120°F
- ⇒ Products should be stored in a dry covered environment
- ⇒ Products should not be stored in warm, direct sunlight
- ⇒ Improper storage conditions can significantly alter the shelf life of the product. Such conditions would include temperature, moisture, open containers, etc.

### PACKAGING AVAILABLE

1/16 oz. Plastic Tub

### Part No.

L0404-016