

Lubriplate's ROBOTIC EP-0 GREASE

Effortless Lubrication for Robotic Precision

Glide through gears with **ease**. Our lithium complex, semi-fluid grease is **expertly crafted** with PAO synthetic hydrocarbon fluids and mineral oil, ensuring enduring performance in **all robotic gear cases**. Our XTREMITY AW/EP additive system delivers unparalleled **protection** against wear, oxidation and corrosion, while its soft consistency ensures **seamless** flow across wide operating temperatures.

Efficient. Protective. Versatile.

Packaging

- | | |
|---------------------------|-----------|
| • Carton of 4 Cartridges | L0415-044 |
| • 35 lb. Pail | L0415-035 |
| • 110 lb. Quarter Drum | L0415-039 |
| • 420 lb. Full Size, Drum | L0415-040 |



Scan to
learn more:



Advantages

- Heat-Defying Lithium Complex Thickener
- Ultimate Protection with XTREMITY AW/EP Additives
- Versatile Performance in Normal to Severe Conditions
- Temperature-Resilient Flow Across Varied Speeds
- Longevity Assured with Shear Stability and Oxidation Resistance



Applications

- Optimized for Robot Gear Reducers
- Ideal for Extreme Pressure NLGI 0 Semi-Fluid Grease
- Tailored Support: Contact Local LUBRIPLATE District Manager

Storage Recommendations

- Maintain Between 40°F-120°F in Dry, Covered Storage
- Avoid Direct Sunlight to Preserve Quality
- Improper Storage Can Compromise Shelf Life

